

ERRATA

On-Site Guide

March 2015

Page 125, Table B6

Please note, Table B6 contained inaccurate values

0.1 to 5 second disconnection times

| Circuit-breaker type | Circuit-breaker rating (amperes) | | | | | | | | | | | | | | |
|----------------------|----------------------------------|-----------------|-----------------|-----------------|-----------------|----------------|-----------------|-----------------|-----------------|------|-----------------|-----------------|-----------------|------|-----------------|
| | 3 | 5 | 6 | 10 | 15 | 16 | 20 | 25 | 30 | 32 | 40 | 45 | 50 | 63 | 100 |
| 1 | 15.5 | 8.8 | 7.73 | 4.4 | 2.93 | 2.76 | 2.2 | 1.76 | 1.47 | 1.38 | 1.1 | 0.98 | 0.88 | 0.7 | 0.44 |
| 1 new | 14.56 | 8.74 | 7.28 | | | | | | | | | | | | |
| 2 | 8.4 | 5.0 | 4.2 | 2.5 | 1.67 | 1.58 | 1.25 | 1.0 | 0.83 | 0.79 | 0.63 | 0.56 | 0.5 | 0.4 | 0.25 |
| B | 11.74 | 7.0 | 5.87 | 3.5 | 2.3 | 2.2 | 1.75 | 1.4 | 1.17 | 1.1 | 0.88 | 0.78 | 0.7 | 0.56 | 0.35 |
| B new | 11.65 | | | | | | | | | | | | | | |
| 3&C | 3.52 | 2.93 | 1.76 | 1.47 | 0.98 | 1.1 | 0.74 | 0.59 | 0.49 | 0.55 | 0.37 | 0.33 | 0.29 | 0.27 | 1.17 |
| 3&C new | 5.82 | 3.49 | 2.91 | 1.75 | 1.16 | 1.09 | 0.87 | 0.7 | 0.58 | 0.44 | 0.38 | 0.35 | 0.35 | 0.17 | 0.17 |

The corrected table is provided below for insertion into your book.

0.1 to 5 second disconnection times

| Circuit-breaker type | Circuit-breaker rating (amperes) | | | | | | | | | | | | | | |
|----------------------|----------------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 3 | 5 | 6 | 10 | 15 | 16 | 20 | 25 | 30 | 32 | 40 | 45 | 50 | 63 | 100 |
| 1 | 14.56 | 8.74 | 7.28 | 4.4 | 2.93 | 2.76 | 2.2 | 1.76 | 1.47 | 1.38 | 1.1 | 0.98 | 0.88 | 0.7 | 0.44 |
| 2 | 8.4 | 5.0 | 4.2 | 2.5 | 1.67 | 1.58 | 1.25 | 1.0 | 0.83 | 0.79 | 0.63 | 0.56 | 0.5 | 0.4 | 0.25 |
| B | 11.65 | 7.0 | 5.87 | 3.5 | 2.3 | 2.2 | 1.75 | 1.4 | 1.17 | 1.1 | 0.88 | 0.78 | 0.7 | 0.56 | 0.35 |
| 3&C | 5.82 | 3.49 | 2.91 | 1.75 | 1.16 | 1.09 | 0.87 | 0.7 | 0.58 | 0.55 | 0.44 | 0.38 | 0.35 | 0.27 | 0.17 |